

## AIR GAP

### STANDARD



50-38

50-T52-RO

50-T52-HF1

P/N	Desc
50-38	Standard
50-T52-RO	w/ 1/4" JG R.O. Port
50-T52-HF1	Dual Dishwasher

### GAP-IT



11-G61S2

11-G61S1

P/N	Desc
11-G61S2	1 1/2"
11-G61S1	2"

### IN-LINE



11-G211211

11-G211212

11-G211213

P/N	Desc
11-G211211	Standard Gap-A-Flow
11-G211212	Hi Flow Gap-A-Flow
11-G211213	Gap-A-Flow Coupling

### STAND PIPE and BARB ADAPTERS



P/N	Desc
17-3208047	w/ 1/2" JG (top), 1/4" JG (side)
17-0860647	1/2" Stem x 3/8" Barb, 45 deg
17-0860847	1/2" Stem x 1/2" Barb, 45 deg
17-0861047	1/2" Stem x 5/8" Barb, 45 deg

## AIR GAP

### DRAIN ADAPTER

P/N	Desc
11-GDLA-D	w/ 3/8" John Guest



### MISTER DRAIN

P/N	Desc
50-6095	



### WALL MOUNT

P/N	Desc
11-G3002	for R.O. Faucet



## WATER PRESSURE GAGE - ANALOG



Side Connect

Rear Connect

P/N	Desc
11-PG100P	100psi, 1/4" MIP Rear Connect
11-PG100S	100psi, 1/4" MIP Side Connect
11-PG140P	140psi, 1/4" MIP Rear Connect
11-PG150S	150psi, 1/4" MIP Side Connect
11-PG300S	300psi, 1/4" MIP Side Connect

## AIR PRESSURE GAGE - DIGITAL



11-PG200

11-PG300

P/N	Desc
11-PG200	0 to 150 psi, w/ Light
11-PG300	0 to 100 psi

## WATER PRESSURE REGULATOR

### PLASTIC



P/N	Desc
06-6P60A	1/4"FIP, 0 to 25psi
06-6P60B	1/4"FIP, 0 to 60psi
06-6P60-4	1/4"FIP, 0 to 125psi

### BRONZE



P/N	Desc
06-W70-12	3/4"FIP x 3/4"FIP
06-W70-16	1"FIP x 1"FIP
06-W70C-12	3/4"FIP x 3/4"CTS
06-W70C-16	1"FIP x 1"CTS
06-W70DUC12	3/4"CTS x 3/4"CTS
06-W600-12	3/4"FIP x 3/4"FIP for High Sediment Water
06-W600-16	1"FIP x 1"FIP for High Sediment Water

## R.O. SYSTEM ANALYZER



This great device allows you to set how many gallons run through each of the R.O. components before a change is necessary. Each component is displayed on the screen with a handy 'gas-gage' indicator. An audible alarm will sound when your predetermined limit is reached.

P/N	Desc
14-FLOWNIC	Monitors Flow and Filter Change

## WATERMINDER METERING VALVE



These unique, patented meter valves provide automatic shut off of a potable water system for filter replacement after a pre-determined quantity of water has been filtered.

Settings in 100 gallon increments.

Operating pressures 15 to 125 psi.

P/N	Desc
14-WM1800	Capacity 1800 gallons
14-WM3800	Capacity 3800 gallons

## TDS METER



P/N	Desc
14-TDS3	0 to 9990ppm, 1ppm steps, w/ Case
14-TDS-EZ	0 to 9990ppm, 1ppm steps, NO Case
14-TDSDUAL	0 to 9990ppm, 1ppm steps, Dual Cup
11-CT10-293	0 to 9990ppm, 1ppm steps, Dual Input
14-TDS1-S	TDS Calibration Solution

## BEAKER, 100 mL

P/N	Desc
14-BKR100	1 mL Steps

